



A P P R O V A L S ®

Certificate of Conformity/Approval

Certificate No.: SAA220636

Certificate Holder: TCI Telecomunicazioni Italia S.r.l.
Via Parma 14,
21047 Saronno (VA)
Italy

Regulatory Definition: Non-Prescribed

Product Description: LED Driver (Built-in)

Standard/s: AS 61347.2.13:2018
AS/NZS 61347.1:2016 Inc A1

Condition/s: Must comply with Standard requirements of end product
when installed.

Approval Marks: RCM (In accordance with AS/NZS 4417 and EESS requirements)
and
SAA220636

Initial Issue Date: 8 November 2022

Expiry Date: 8 November 2027

R. A. Hill

For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

www.saaapprovals.com.au

JAS-ANZ



www.jas-anz.org/register



Issued: 08-11-22 220636
Page 1 of 2



A P P R O V A L S ®

Certificate of Conformity/Approval

Model	Trade Name	Rating/Marking
ASTRO 40W/350-1050 2PN	TCI LED	Input: 200-240V~ 50/60Hz, 0.3A Max Output: 20-57Vdc, 0.35-1.050A, Max 40W, Max Uout 70Vdc ta: -40°C to +55°C, tc: 85°C, Symbol for built-in control gear with Double or reinforced insulation.
ASTRO 80W/350-1050 2PN	TCI LED	Input: 200-240V~ 50/60Hz, 0.65A Max Output: 35-115Vdc, 0.35-1.050A, Max 80W, Max Uout 140Vdc ta: -40°C to +55°C, tc: 85°C, Symbol for built-in control gear with Double or reinforced insulation.
ASTRO 120W/350-1050 2PN	TCI LED	Input: 200-240V~ 50/60Hz, 1.0A Max Output: 75-172Vdc, 0.35-1.050A, Max 120W, Max Uout 200Vdc ta: -40°C to +55°C, tc: 85°C, Symbol for built-in control gear with Double or reinforced insulation.
ASTRO 165W/350-1050 2PN	TCI LED	Input: 200-240V~ 50/60Hz, 1.26A Max Output: 105-236Vdc, 0.35-1.050A, Max 165W, Max Uout 260Vdc ta: -40°C to +50°C, tc: 90°C, Symbol for built-in control gear with Double or reinforced insulation.
ASTRO 200W/350-1050 2PN	TCI LED	Input: 200-240V~ 50/60Hz, 1.60A Max Output: 143-286Vdc, 0.35-1.050A, Max 165W, Max Uout 310Vdc ta: -40°C to +50°C, tc: 90°C, Symbol for built-in control gear with Double or reinforced insulation.

R. A. Hill


For and on Behalf of
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

www.saaapprovals.com.au

JAS-ANZ



www.jas-anz.org/register



Issued: 08-11-22 220636
Page 2 of 2