

Certificate of Suitability

Global-Mark Pty. Ltd., certify the electrical equipment described hereunder complies with standards listed herein and notifies the certificate holder to affix the Regulatory Compliance Mark (RCM) mark on the product of the same type provided that the requirements of all relevant parts of AS/NZS 4417 applicable to the article are fulfilled. In placing the RCM mark on the product, the Responsible Supplier makes a declaration of compliance with the certification standard(s) and confirms that the product is identical to the product certified herein. This Certificate meets the requirements of a Recognised External Certification Scheme (RECS).

CERTIFICATION AND CERTIFICATE HOLDER DETAILS

Company Name	TCI Telecomunicazioni Italia S.R.L.	Other Name	
Address	Via Parma 14 Saronno Varese 21047 Italy		
Client ID	105895	Global-Mark File Number:	105895-080
Certification Number	GMA-521874	Revision Number	00
Certificate Standard(s)	AS 61347.2.13:2018 & AS/NZS 61347.1:2016 Amd 1: 2018 Lamp Control Gear - Part 2-13: Particular Requirements For D.C Or A.C Supplied Electronic Control Gear For Led Modules.		
Type of Certification	Electrical Safety Product	Scheme	Global-Mark Electrical Product Safety Certification Scheme

System 1 Approval

CERTIFICATE DATES

Certificate Issue Date	7/02/2025
Certificate Last Update Date	
Certification Expiry Date	7/02/2030

This certification remains valid until the above-mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jasanz.org/register for verification.



Certification Manager



Page 1 of 7

Global-Mark Pty Ltd, Copyright 2012 - 407, 32 Delhi Road, North Ryde NSW 2113, Australia



Certificate of Suitability

CERTIFIED ELECTRICAL EQUIPMENT				
Declared Article	Product Description	Trade Name	Model Number	Rating
Non declared	Power Supply for LED module	TCI	MSE 18/350 SLIM cod. 127403 CN	Vin=220-240 V 50-60 Hz 0,12 A Pin=22 W; Po=10,8-18,9 W Io=0,2-0,35 A Uout=60 V
Non declared	Power Supply for LED module	TCI	MSE 18/350 SLIM cod. 127403 T CN	Vin=220-240 V 50-60 Hz 0,12 A Pin=22 W; Po=10,8-18,9 W Io=0,2-0,35 A Uout=60 V
Non declared	Power Supply for LED module	TCI	MSE 42/800 SLIM cod. 127404 CN	Vin=220-240 V 50-60 Hz 0,23 A Pin=49,3 W; Po=27-43,2 W Io=0,5-0,8 A Uout=60 V
Non declared	Power Supply for LED module	TCI	MSE 42/800 SLIM cod. 127404 T CN	Vin=220-240 V 50-60 Hz 0,23 A Pin=49,3 W; Po=27-43,2 W Io=0,5-0,8 A Uout=60 V
Non declared	Power Supply for LED module	TCI	MSE 60/1200 SLIM cod. 127405 CN	Vin=220-240 V 50-60 Hz 0,32 A Pin=70,1 W; Po=48,6-61,2 W Io=0,9-1,2 A Uout=60 V
Non declared	Power Supply for LED module	TCI	MSE 60/1200 SLIM cod. 127405 T CN	Vin=220-240 V 50-60 Hz 0,32 A Pin=70,1 W; Po=48,6-61,2 W Io=0,9-1,2 A Uout=60 V
Non declared	Power Supply for LED module	TCI	MSE 75/1600 SLIM cod. 127406 CN	Vin=220-240 V 50-60 Hz 0,39 A Pin=86 W; Po=70,2-76,8 W Io=1,3-1,6 A Uout=60 V
Non declared	Power Supply for LED module	TCI	MSE 75/1600 SLIM cod. 127406 T CN	Vin=220-240 V 50-60 Hz 0,39 A Pin=86 W; Po=70,2-76,8 W Io=1,3-1,6 A Uout=60 V
Non declared	Power Supply for LED module	TCI	MSE 18/350 SLIM cod. 127403I	Vin=220-240 V 50-60 Hz 0,12 A Pin=22 W; Po=10,8-18,9 W Io=0,2-0,35 A Uout=60 V
Non declared	Power Supply for LED module	TCI	MSE 18/350 SLIM cod. 127403I T	Vin=220-240 V 50-60 Hz 0,12 A Pin=22 W; Po=10,8-18,9 W Io=0,2-0,35 A Uout=60 V
Non declared	Power Supply for LED module	TCI	MSE 42/800 SLIM cod. 127404I	Vin=220-240 V 50-60 Hz 0,23 A Pin=49,3 W; Po=27-43,2 W Io=0,5-0,8 A Uout=60 V
Non declared	Power Supply for LED module	TCI	MSE 42/800 SLIM cod. 127404I T	Vin=220-240 V 50-60 Hz 0,23 A Pin=49,3 W; Po=27-43,2 W Io=0,5-0,8 A Uout=60 V
Non declared	Power Supply for LED module	TCI	MSE 60/1200 SLIM cod. 127405I	Vin=220-240 V 50-60 Hz 0,32 A Pin=70,1 W; Po=48,6-61,2 W Io=0,9-1,2 A Uout=60 V

This certification remains valid until the above-mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jasanz.org/register for verification.



Certification Manager

Page 2 of 7

Certificate of Suitability

Non declared	Power Supply for LED module	TCI	MSE 60/1200 SLIM cod. 127405I T	Vin=220-240 V 50-60 Hz 0,32 A Pin=70,1 W; Po=48,6-61,2 W Io=0,9-1,2 A Uout=60 V
Non declared	Power Supply for LED module	TCI	MSE 75/1600 SLIM cod. 127406I	Vin=220-240 V 50-60 Hz 0,39 A Pin=86 W; Po=70,2-76,8 W Io=1,3-1,6 A Uout=60 V
Non declared	Power Supply for LED module	TCI	MSE 75/1600 SLIM cod. 127406I T	Vin=220-240 V 50-60 Hz 0,39 A Pin=86 W; Po=70,2-76,8 W Io=1,3-1,6 A Uout=60 V
Non declared	Power Supply for LED module	TN101	MSE 18/350 SLIM cod. 127403 CN	Vin=220-240 V 50-60 Hz 0,12 A Pin=22 W; Po=10,8-18,9 W Io=0,2-0,35 A Uout=60 V
Non declared	Power Supply for LED module	TN101	MSE 18/350 SLIM cod. 127403 T CN	Vin=220-240 V 50-60 Hz 0,12 A Pin=22 W; Po=10,8-18,9 W Io=0,2-0,35 A Uout=60 V
Non declared	Power Supply for LED module	TN101	MSE 42/800 SLIM cod. 127404 CN	Vin=220-240 V 50-60 Hz 0,23 A Pin=49,3 W; Po=27-43,2 W Io=0,5-0,8 A Uout=60 V
Non declared	Power Supply for LED module	TN101	MSE 42/800 SLIM cod. 127404 T CN	Vin=220-240 V 50-60 Hz 0,23 A Pin=49,3 W; Po=27-43,2 W Io=0,5-0,8 A Uout=60 V
Non declared	Power Supply for LED module	TN101	MSE 60/1200 SLIM cod. 127405 CN	Vin=220-240 V 50-60 Hz 0,32 A Pin=70,1 W; Po=48,6-61,2 W Io=0,9-1,2 A Uout=60 V
Non declared	Power Supply for LED module	TN101	MSE 60/1200 SLIM cod. 127405 T CN	Vin=220-240 V 50-60 Hz 0,32 A Pin=70,1 W; Po=48,6-61,2 W Io=0,9-1,2 A Uout=60 V
Non declared	Power Supply for LED module	TN101	MSE 75/1600 SLIM cod. 127406 CN	Vin=220-240 V 50-60 Hz 0,39 A Pin=86 W; Po=70,2-76,8 W Io=1,3-1,6 A Uout=60 V
Non declared	Power Supply for LED module	TN101	MSE 75/1600 SLIM cod. 127406 T CN	Vin=220-240 V 50-60 Hz 0,39 A Pin=86 W; Po=70,2-76,8 W Io=1,3-1,6 A Uout=60 V
Non declared	Power Supply for LED module	TN101	MSE 18/350 SLIM cod. 127403I	Vin=220-240 V 50-60 Hz 0,12 A Pin=22 W; Po=10,8-18,9 W Io=0,2-0,35 A Uout=60 V
Non declared	Power Supply for LED module	TN101	MSE 18/350 SLIM cod. 127403I T	Vin=220-240 V 50-60 Hz 0,12 A Pin=22 W; Po=10,8-18,9 W Io=0,2-0,35 A Uout=60 V
Non declared	Power Supply for LED module	TN101	MSE 42/800 SLIM cod. 127404I	Vin=220-240 V 50-60 Hz 0,23 A Pin=49,3 W; Po=27-43,2 W Io=0,5-0,8 A Uout=60 V
Non declared	Power Supply for LED module	TN101	MSE 42/800 SLIM cod. 127404I T	Vin=220-240 V 50-60 Hz 0,23 A Pin=49,3 W; Po=27-43,2 W Io=0,5-0,8 A Uout=60 V

This certification remains valid until the above-mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jasanz.org/register for verification.



Certification Manager

Page 3 of 7

Certificate of Suitability

Non declared	Power Supply for LED module	TN101	MSE 60/1200 SLIM cod. 127405I	Vin=220-240 V 50-60 Hz 0,32 A Pin=70,1 W; Po=48,6-61,2 W Io=0,9-1,2 A Uout=60 V
Non declared	Power Supply for LED module	TN101	MSE 60/1200 SLIM cod. 127405I T	Vin=220-240 V 50-60 Hz 0,32 A Pin=70,1 W; Po=48,6-61,2 W Io=0,9-1,2 A Uout=60 V
Non declared	Power Supply for LED module	TN101	MSE 75/1600 SLIM cod. 127406I	Vin=220-240 V 50-60 Hz 0,39 A Pin=86 W; Po=70,2-76,8 W Io=1,3-1,6 A Uout=60 V
Non declared	Power Supply for LED module	TN101	MSE 75/1600 SLIM cod. 127406I T	Vin=220-240 V 50-60 Hz 0,39 A Pin=86 W; Po=70,2-76,8 W Io=1,3-1,6 A Uout=60 V
Non declared	Power Supply for LED module	TCI LIGHT Saronno Italy	MSE 18/350 SLIM cod. 127403 CN	Vin=220-240 V 50-60 Hz 0,12 A Pin=22 W; Po=10,8-18,9 W Io=0,2-0,35 A Uout=60 V
Non declared	Power Supply for LED module	TCI LIGHT Saronno Italy	MSE 18/350 SLIM cod. 127403 T CN	Vin=220-240 V 50-60 Hz 0,12 A Pin=22 W; Po=10,8-18,9 W Io=0,2-0,35 A Uout=60 V
Non declared	Power Supply for LED module	TCI LIGHT Saronno Italy	MSE 42/800 SLIM cod. 127404 CN	Vin=220-240 V 50-60 Hz 0,23 A Pin=49,3 W; Po=27-43,2 W Io=0,5-0,8 A Uout=60 V
Non declared	Power Supply for LED module	TCI LIGHT Saronno Italy	MSE 42/800 SLIM cod. 127404 T CN	Vin=220-240 V 50-60 Hz 0,23 A Pin=49,3 W; Po=27-43,2 W Io=0,5-0,8 A Uout=60 V
Non declared	Power Supply for LED module	TCI LIGHT Saronno Italy	MSE 60/1200 SLIM cod. 127405 CN	Vin=220-240 V 50-60 Hz 0,32 A Pin=70,1 W; Po=48,6-61,2 W Io=0,9-1,2 A Uout=60 V
Non declared	Power Supply for LED module	TCI LIGHT Saronno Italy	MSE 60/1200 SLIM cod. 127405 T CN	Vin=220-240 V 50-60 Hz 0,32 A Pin=70,1 W; Po=48,6-61,2 W Io=0,9-1,2 A Uout=60 V
Non declared	Power Supply for LED module	TCI LIGHT Saronno Italy	MSE 75/1600 SLIM cod. 127406 CN	Vin=220-240 V 50-60 Hz 0,39 A Pin=86 W; Po=70,2-76,8 W Io=1,3-1,6 A Uout=60 V
Non declared	Power Supply for LED module	TCI LIGHT Saronno Italy	MSE 75/1600 SLIM cod. 127406 T CN	Vin=220-240 V 50-60 Hz 0,39 A Pin=86 W; Po=70,2-76,8 W Io=1,3-1,6 A Uout=60 V
Non declared	Power Supply for LED module	TCI LIGHT Saronno Italy	MSE 18/350 SLIM cod. 127403I	Vin=220-240 V 50-60 Hz 0,12 A Pin=22 W; Po=10,8-18,9 W Io=0,2-0,35 A Uout=60 V
Non declared	Power Supply for LED module	TCI LIGHT Saronno Italy	MSE 18/350 SLIM cod. 127403I T	Vin=220-240 V 50-60 Hz 0,12 A Pin=22 W; Po=10,8-18,9 W Io=0,2-0,35 A Uout=60 V
Non declared	Power Supply for LED module	TCI LIGHT Saronno Italy	MSE 42/800 SLIM cod. 127404I	Vin=220-240 V 50-60 Hz 0,23 A Pin=49,3 W; Po=27-43,2 W Io=0,5-0,8 A Uout=60 V

This certification remains valid until the above-mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jasanz.org/register for verification.



Certification Manager

Page 4 of 7

Certificate of Suitability

Non declared	Power Supply for LED module	TCI LIGHT Saronno Italy	MSE 42/800 SLIM cod. 127404I T	Vin=220-240 V 50-60 Hz 0,23 A Pin=49,3 W; Po=27-43,2 W Io=0,5-0,8 A Uout=60 V
Non declared	Power Supply for LED module	TCI LIGHT Saronno Italy	MSE 60/1200 SLIM cod. 127405I	Vin=220-240 V 50-60 Hz 0,32 A Pin=70,1 W; Po=48,6-61,2 W Io=0,9-1,2 A Uout=60 V
Non declared	Power Supply for LED module	TCI LIGHT Saronno Italy	MSE 60/1200 SLIM cod. 127405I T	Vin=220-240 V 50-60 Hz 0,32 A Pin=70,1 W; Po=48,6-61,2 W Io=0,9-1,2 A Uout=60 V
Non declared	Power Supply for LED module	TCI LIGHT Saronno Italy	MSE 75/1600 SLIM cod. 127406I	Vin=220-240 V 50-60 Hz 0,39 A Pin=86 W; Po=70,2-76,8 W Io=1,3-1,6 A Uout=60 V
Non declared	Power Supply for LED module	TCI LIGHT Saronno Italy	MSE 75/1600 SLIM cod. 127406I T	Vin=220-240 V 50-60 Hz 0,39 A Pin=86 W; Po=70,2-76,8 W Io=1,3-1,6 A Uout=60 V
Non declared	Power Supply for LED module	TCI LIGHT	MSE 18/350 SLIM cod. 127403 CN	Vin=220-240 V 50-60 Hz 0,12 A Pin=22 W; Po=10,8-18,9 W Io=0,2-0,35 A Uout=60 V
Non declared	Power Supply for LED module	TCI LIGHT	MSE 18/350 SLIM cod. 127403 T CN	Vin=220-240 V 50-60 Hz 0,12 A Pin=22 W; Po=10,8-18,9 W Io=0,2-0,35 A Uout=60 V
Non declared	Power Supply for LED module	TCI LIGHT	MSE 42/800 SLIM cod. 127404 CN	Vin=220-240 V 50-60 Hz 0,23 A Pin=49,3 W; Po=27-43,2 W Io=0,5-0,8 A Uout=60 V
Non declared	Power Supply for LED module	TCI LIGHT	MSE 42/800 SLIM cod. 127404 T CN	Vin=220-240 V 50-60 Hz 0,23 A Pin=49,3 W; Po=27-43,2 W Io=0,5-0,8 A Uout=60 V
Non declared	Power Supply for LED module	TCI LIGHT	MSE 60/1200 SLIM cod. 127405 CN	Vin=220-240 V 50-60 Hz 0,32 A Pin=70,1 W; Po=48,6-61,2 W Io=0,9-1,2 A Uout=60 V
Non declared	Power Supply for LED module	TCI LIGHT	MSE 60/1200 SLIM cod. 127405 T CN	Vin=220-240 V 50-60 Hz 0,32 A Pin=70,1 W; Po=48,6-61,2 W Io=0,9-1,2 A Uout=60 V
Non declared	Power Supply for LED module	TCI LIGHT	MSE 75/1600 SLIM cod. 127406 CN	Vin=220-240 V 50-60 Hz 0,39 A Pin=86 W; Po=70,2-76,8 W Io=1,3-1,6 A Uout=60 V
Non declared	Power Supply for LED module	TCI LIGHT	MSE 75/1600 SLIM cod. 127406 T CN	Vin=220-240 V 50-60 Hz 0,39 A Pin=86 W; Po=70,2-76,8 W Io=1,3-1,6 A Uout=60 V
Non declared	Power Supply for LED module	TCI LIGHT	MSE 18/350 SLIM cod. 127403I	Vin=220-240 V 50-60 Hz 0,12 A Pin=22 W; Po=10,8-18,9 W Io=0,2-0,35 A Uout=60 V
Non declared	Power Supply for LED module	TCI LIGHT	MSE 18/350 SLIM cod. 127403I T	Vin=220-240 V 50-60 Hz 0,12 A Pin=22 W; Po=10,8-18,9 W Io=0,2-0,35 A Uout=60 V

This certification remains valid until the above-mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jasanz.org/register for verification.



Certification Manager

Page 5 of 7

Global-Mark Pty Ltd, Copyright 2012 - 407, 32 Delhi Road, North Ryde NSW 2113, Australia



Certificate of Suitability

Non declared	Power Supply for LED module	TCI LIGHT	MSE 42/800 SLIM cod. 127404I	Vin=220-240 V 50-60 Hz 0,23 A Pin=49,3 W; Po=27-43,2 W Io=0,5-0,8 A Uout=60 V
Non declared	Power Supply for LED module	TCI LIGHT	MSE 42/800 SLIM cod. 127404I T	Vin=220-240 V 50-60 Hz 0,23 A Pin=49,3 W; Po=27-43,2 W Io=0,5-0,8 A Uout=60 V
Non declared	Power Supply for LED module	TCI LIGHT	MSE 60/1200 SLIM cod. 127405I	Vin=220-240 V 50-60 Hz 0,32 A Pin=70,1 W; Po=48,6-61,2 W Io=0,9-1,2 A Uout=60 V
Non declared	Power Supply for LED module	TCI LIGHT	MSE 60/1200 SLIM cod. 127405I T	Vin=220-240 V 50-60 Hz 0,32 A Pin=70,1 W; Po=48,6-61,2 W Io=0,9-1,2 A Uout=60 V
Non declared	Power Supply for LED module	TCI LIGHT	MSE 75/1600 SLIM cod. 127406I	Vin=220-240 V 50-60 Hz 0,39 A Pin=86 W; Po=70,2-76,8 W Io=1,3-1,6 A Uout=60 V
Non declared	Power Supply for LED module	TCI LIGHT	MSE 75/1600 SLIM cod. 127406I T	Vin=220-240 V 50-60 Hz 0,39 A Pin=86 W; Po=70,2-76,8 W Io=1,3-1,6 A Uout=60 V
Non declared	Power Supply for LED module	TCI LED	MSE 18/350 SLIM cod. 127403 CN	Vin=220-240 V 50-60 Hz 0,12 A Pin=22 W; Po=10,8-18,9 W Io=0,2-0,35 A Uout=60 V
Non declared	Power Supply for LED module	TCI LED	MSE 18/350 SLIM cod. 127403 T CN	Vin=220-240 V 50-60 Hz 0,12 A Pin=22 W; Po=10,8-18,9 W Io=0,2-0,35 A Uout=60 V
Non declared	Power Supply for LED module	TCI LED	MSE 42/800 SLIM cod. 127404 CN	Vin=220-240 V 50-60 Hz 0,23 A Pin=49,3 W; Po=27-43,2 W Io=0,5-0,8 A Uout=60 V
Non declared	Power Supply for LED module	TCI LED	MSE 42/800 SLIM cod. 127404 T CN	Vin=220-240 V 50-60 Hz 0,23 A Pin=49,3 W; Po=27-43,2 W Io=0,5-0,8 A Uout=60 V
Non declared	Power Supply for LED module	TCI LED	MSE 60/1200 SLIM cod. 127405 CN	Vin=220-240 V 50-60 Hz 0,32 A Pin=70,1 W; Po=48,6-61,2 W Io=0,9-1,2 A Uout=60 V
Non declared	Power Supply for LED module	TCI LED	MSE 60/1200 SLIM cod. 127405 T CN	Vin=220-240 V 50-60 Hz 0,32 A Pin=70,1 W; Po=48,6-61,2 W Io=0,9-1,2 A Uout=60 V
Non declared	Power Supply for LED module	TCI LED	MSE 75/1600 SLIM cod. 127406 CN	Vin=220-240 V 50-60 Hz 0,39 A Pin=86 W; Po=70,2-76,8 W Io=1,3-1,6 A Uout=60 V
Non declared	Power Supply for LED module	TCI LED	MSE 75/1600 SLIM cod. 127406 T CN	Vin=220-240 V 50-60 Hz 0,39 A Pin=86 W; Po=70,2-76,8 W Io=1,3-1,6 A Uout=60 V
Non declared	Power Supply for LED module	TCI LED	MSE 18/350 SLIM cod. 127403I	Vin=220-240 V 50-60 Hz 0,12 A Pin=22 W; Po=10,8-18,9 W Io=0,2-0,35 A Uout=60 V

This certification remains valid until the above-mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jasanz.org/register for verification.



Certification Manager

Page 6 of 7

Certificate of Suitability

Non declared	Power Supply for LED module	TCI LED	MSE 18/350 SLIM cod. 127403I T	Vin=220-240 V 50-60 Hz 0,12 A Pin=22 W; Po=10,8-18,9 W Io=0,2-0,35 A Uout=60 V
Non declared	Power Supply for LED module	TCI LED	MSE 42/800 SLIM cod. 127404I	Vin=220-240 V 50-60 Hz 0,23 A Pin=49,3 W; Po=27-43,2 W Io=0,5-0,8 A Uout=60 V
Non declared	Power Supply for LED module	TCI LED	MSE 42/800 SLIM cod. 127404I T	Vin=220-240 V 50-60 Hz 0,23 A Pin=49,3 W; Po=27-43,2 W Io=0,5-0,8 A Uout=60 V
Non declared	Power Supply for LED module	TCI LED	MSE 60/1200 SLIM cod. 127405I	Vin=220-240 V 50-60 Hz 0,32 A Pin=70,1 W; Po=48,6-61,2 W Io=0,9-1,2 A Uout=60 V
Non declared	Power Supply for LED module	TCI LED	MSE 60/1200 SLIM cod. 127405I T	Vin=220-240 V 50-60 Hz 0,32 A Pin=70,1 W; Po=48,6-61,2 W Io=0,9-1,2 A Uout=60 V
Non declared	Power Supply for LED module	TCI LED	MSE 75/1600 SLIM cod. 127406I	Vin=220-240 V 50-60 Hz 0,39 A Pin=86 W; Po=70,2-76,8 W Io=1,3-1,6 A Uout=60 V
Non declared	Power Supply for LED module	TCI LED	MSE 75/1600 SLIM cod. 127406I T	Vin=220-240 V 50-60 Hz 0,39 A Pin=86 W; Po=70,2-76,8 W Io=1,3-1,6 A Uout=60 V

RELEVANT TRADEMARK (S)



COMMENTS OR CONDITIONS ON THE CERTIFICATION

2025/02/07 Initial Certification

Classified as Built in Power supply for lighting purposes for use with class III LED lighting

End of document

This certification remains valid until the above-mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jasanz.org/register for verification.



Certification Manager



Page 7 of 7

Global-Mark Pty Ltd, Copyright 2012 - 407, 32 Delhi Road, North Ryde NSW 2113, Australia

