



# DOLPHIN T CLASSE II IP67



Serie "DOLPHIN T" trasformatore toroidali carenati IP67  
Series "DOLPHIN T" IP67 cowled toroidal transformers



Articolo Article	Codice Code	Potenza Power VA	Tensione Voltage (in/out) V	Protezione Protection	Dimensioni Dimensions		Peso Weight gr.	Colore Colour	Confezioni Box
					ØD	H			
DLT 50	148750	50	230/12	TA	100	111	700	Nero - Black	10
DLT 60	148756	60	230/12	TA	100	111	900	Nero - Black	10
DLT 80	148757	80	230/12	TA	100	111	1100	Nero - Black	10
DLT 105	148752A	105	230/12	TA	100	111	1260	Nero - Black	10

Trasformatore toroidali  
Toroidal transformers

**Norme di riferimento**  
**Reference Norms:**  
EN 61558-1  
EN 61558-2-6  
VDE 0710.T14

**Tensione Voltage**  
230 V - 12 V

**Frequenza Frequency**  
0/50...60 Hz

**Potenza Power**  
50 ÷ 100 VA

- Trasformatore protetto in classe II, IP67.
  - Specifico per l'utilizzo in luoghi esterni.
  - Il trasformatore è fornito di speciale fissacavo per garantire la tenuta stagna.
  - Protezione termica e al cortocircuito.
  - Protezione contro i sovraccarichi.
- A richiesta lunghezza cavi max. 200 cm.**  
**A richiesta disponibile versione 120 o 240 V.**

- IP67 transformers with class II protection.
  - Specially designed for outdoor installation.
  - The transformer is complete with a special cable retainer to guarantee perfect sealing.
  - Protected against overheating and short-circuits.
  - Protected against overloads.
- Cable max. length 200 cm upon request.**  
**120 or 240 V version available upon request.**

0,5 - 1,5 □

