
# LINEA FLAT 33LED

**Lenses**







(Weight/Peso 2,15 oz. / gr. 61)






RESIDENTIAL OFFICE RETAIL INDUSTRY

| Article<br>Articolo | LINEA FLAT 33LED | LINEA FLAT 33LED | LINEA FLAT 33LED | LINEA FLAT 33LED |
|---|---|---|---|---|
| Beam Angle<br>Angolo di orientamento | 30° | 60° | 90° | Double asymmetric<br>Doppia asimmetrica |
| Code<br>Codice | 468780112 | 468780113 | 468780114 | 468780115 |
| Polar distribution<br>Distribuzione polare |  |  |  |  |



## Technical notes for Optics

- Uniform light distribution
- High efficiency
- Ideal for residential, office, retail and industrial lighting
- Material: Optical Grade PMMA 8N
- Dimensions (LxWxH): 286x61x10 mm
- Max allowed temperature: -40...90°C
- Fixing with flat head screws. Tightening torque: 0,48 Nm
- Packaging unit: 210 pcs

## Note tecniche per le Ottiche

- Distribuzione di luce uniforme
- Alta efficienza
- Ideali per illuminazione residenziale, uffici, spazi commerciali e industriali
- Materiale: Optical Grade PMMA 8N
- Dimensioni (LxWxH): 286x61x10 mm
- Temperatura massima: -40...90°C
- Fissaggio tramite viti a testa piatta. Coppia di serraggio: 0,48 Nm
- Confezione da 210 pezzi

WARRANTY 10 YEARS NO YELLOWING

FLAME RATING UL94 HB

**For additional technical informations see www.tci.it**