

## Conditions of Acceptability:

Use - For use only in (or with) complete equipment where the acceptability of the combination is determined by UL LLC.

1. These products been evaluated for the following characteristics.

Model No.			Product is rated
DC 8W 12V XXX	Input type- Branch Circuit (Mains)	Output type: CV Output is Class 2 (a)	Dry, Damp
DC 15W 700mA XXX	Input type- Branch Circuit (Mains)	Output type: CC Output is Class 2 (a)	Dry, Damp
DC 15W 700mA XXX	Input type- Branch Circuit (Mains)	Output type: CC Output is Class 2(a)	Dry, Damp

a- As defined in UL 8750, Clause 7.12.1, and CAN/CSA-C22.2 No. 250.13, Clause 8.12.1

2. Rated output loading for these products was achieved using a resistive load.
3. The temperature tests were performed at nominal **55°C** ambient temperature, with the measured maximum temperature on outer case of **84°C**. Acceptable operation at a higher temperature shall be determined in the end product.
4. These products utilize a UL Recognized OBJY2 Class B (130) electrical insulation system for the isolation transformer T1.
5. These products are intended for building-in. Acceptability of the LED driver- with respect to mounting, spacing, casualty, temperature and segregation- is to be determined as part of the end device evaluation.
6. These LED drivers are intended to be operated in a maximum 20 A branch circuit.
7. These products are provided with set-screw terminals block for supply and load connections. The supply connector are intended for use with 26-14 AWG solid/stranded copper conductors.
- \*
8. The output of units with suffix RS, RSBI, R and RBI are intended to be dimmable using a digital PWM signal. This interface is a sink, since the interface circuit operates from an external source of supply.
9. **The models integrally provided with strain relief means, have been subjected at Mold Stress and Strain Relief Test at 156 N by using supply cord (Not Provided with unit) type SPT-2 (2x18 AWG) and SVT (2x18 AWG) and 89 N by using a lead wire type 1015. Suitability with a different cord or cable shall be considered in the end product.**
10. **A five-inch flame test was conducted per UL 1598. The Polymeric Housing has been found comply with 5VA flammability when temperature does not exceed 100°C in the end use on this part.**