



# 中国强制性产品认证印刷 / 模压标志批准书

Permission of Printing/Impressing China Compulsory Product Certification Mark

No.FZ1601006195

兹批准本通知书申请人在由下列生产厂为其生产的产品铭牌上使用印刷方式加施强制性产品标志。

WE HEREBY AUTHORIZE THE APPLICANT IN THE FACTORY TO ADOPT  
PRINTED USING COMPULSORY CERTIFICATION MARK.THE APPROVED  
DESIGN OF MARKS MUST BE SHOWN ON THE NAMEPLATE OF PRODUCTS.

申 请 人: TCI Telecomunicazioni Italia S.r.l.

APPLICANT:

制 造 商: TCI Telecomunicazioni Italia S.r.l.

MANUFACTURER:

生 产 厂: TCI Telecomunicazioni Italia S.r.l.

FACTORY:

证 书 号: 2015011002833780(共有5张证书,其他证书见附页。)

CERTIFICATE NO:

批准图案(见附页)

APPROVED PATTERN (SEE ATTACHMENT)

发证日期:2016年02月24日  
APPLICATION DATE:Feb.24, 2016

审核专用章



# 中国强制性产品认证印刷 / 模压标志批准书

Permission of Printing/Impressing China Compulsory Product Certification Mark

FZ1601006195

2015011002833780 2015011002833781 2015011002824244 2015011002826483  
2015011002823917 \*

此批准书批准范围仅为CCC认证证书涵盖内容，批复图案中无关CCC证书的内容不在批准范围内，请认证企业遵照相关法律法规执行。《中国强制性产品认证印刷/模压标志批准书》有效期内，如所涉及CCC认证证书失效，则批准书同时失效。

IT IS ONLY THE AREAS COVERED BY CCC CERTIFICATE ARE AUTHORIZED. THE IRRELEVANT CONTENT OF THE APPROVED DESIGNS CAN NOT BE AUTHORIZED. THE CERTIFIED ORGANIZATIONS SHOULD BE SUBJECT TO THE RELEVANT LAWS AND REGULATIONS. DURING THE VALID PERIOD OF "PERMISSION OF PRINTING/IMPRESSING CHINA COMPULSORY CERTIFICATION MARK", IF THE RELEVANT CCC CERTIFICATE EXPIRES, THE APPROVAL AUTOMATICALLY EXPIRES.

产品类别：1002，标志类型：S&EMC，标志制作方式：印刷，  
标志加施位置：铭牌，标志尺寸：8.6毫米，标志颜色：黑色。

**TCI** 06/15 **SMART 50**  
AC/DC P/S for LED  
LED控制装置  
cod. 122220

MADE IN ITALY

PRI: 220-240V~ 0/50/60Hz; I<sub>max</sub>=0,25A; λ=0,95  
SEC: 350-1050mA (C.C.); Po=27-50W; Vomax=85V~  
ta=25...45/60°C; tc= 90°C

ENEC 05 KEMA EMC CCC S&E

220...240V	ta max	SEC	Vout	4	3	2	1
27 W	80 °C	350 mA	10-78 V	-	-	-	-
31 W	80 °C	400 mA	10-78 V	-	-	-	ON
35 W	55 °C	450 mA	10-78 V	-	-	ON	-
39 W	55 °C	500 mA	10-78 V	-	-	ON	ON
43 W	50 °C	550 mA	10-78 V	-	ON	-	-
45 W	50 °C	600 mA	10-75 V	-	ON	-	ON
47 W	45 °C	650 mA	10-72 V	-	ON	ON	-
50 W	45 °C	700 mA	10-71 V	-	ON	ON	ON
50 W	45 °C	750 mA	10-68 V	ON	-	-	-
50 W	45 °C	800 mA	10-62 V	ON	-	-	ON
50 W	45 °C	850 mA	10-59 V	ON	-	ON	-
50 W	45 °C	900 mA	10-55 V	ON	-	ON	ON
50 W	45 °C	950 mA	10-53 V	ON	ON	-	-
50 W	45 °C	1000 mA	10-50 V	ON	ON	-	ON
50 W	45 °C	1050 mA	10-48 V	ON	ON	ON	-

Before use, always check S1 dipswitch setting  
每次使用前请检查拨码开关 S1 的设置

4 3 2 1 S1  
ON

SELV SEC  
NTC +  
+

CE

M M 110

EL F

25mm

tc

PRI 0.75-1.5  
/ SEC 0.5-1.5

20-18 AWG

8-9mm

PRI

N

L