



Certificate of Approval

Certificate No.: SAA-141682-EA

Date of Issue: 15 September 2014

Certificate Holder: TCI Telecomunicazioni Italia S.r.l.
Via Parma 14,
21047 Saronno (VA)
Italy

Class Description: Power Supply or Charger
Product Description: Independent SELV Dimmable LED Driver
Brand Name: TCI
Model No.: DC MAXI JOLLY US
Markings: Input: 100-240V~ 50/60Hz 0.25-0.55A or 170-280Vdc
Output: 25-55W; 350-1050mA, Max 90Vdc; or
48Vdc, Max 1050mA
t_c:85°C
Standard: AS/NZS IEC 61347.2.13:2013
Conditions: Nil

Approval Mark: SAA-141682-EA or RCM


Date First Registered: 15 September 2014

Date of Expiry: 15 September 2019

For and on Behalf of
SAA Approvals Pty Ltd

SAA Approvals Pty Ltd Electrical Product Safety Certification Scheme as accredited by JAS-ANZ under ISO/IEC Guide 65 certifies that the electrical product described on this certificate complies with the minimum electrical safety requirements for which the application has been made.

For SAA Contact Details and to verify this Certificate go to:
www.saaapprovals.com.au



www.jas-anz.org/register



141682/1



APPROVALS®

Certificate of Approval

Addendum

Certificate No.: SAA-141682-EA

Date of Issue: 15 September 2014

Class Description: Power Supply or Charger
Product Description: Independent SELV Dimmable LED Driver

General Modification:

Use of alternative trade name TN101.

Additional Models

MP 50 K3

MP 50 PR K3

MP 50 TCM

MP 50 PR TCM

DC MAXI JOLLY US TCM

DC MAXI JOLLY US DALI

DC MAXI JOLLY US DALI TCM

DC MAXI JOLLY US MIDNIGHT

DC MAXI JOLLY US MIDNIGHT TCM

DC MAXI JOLLY US BILEVEL

DC MAXI JOLLY US BILEVEL TCM

DC MAXI JOLLY US BILEVEL N

DC MAXI JOLLY US BILEVEL N TCM

DC MAXI JOLLY US PLV

DC MAXI JOLLY US PLV TCM

Description

Similar to DC MAXI JOLLY US except not dimmable.

Similar to MP 50 K3 except with PR terminal.

Similar to MP 50 K3 except for enclosure and t_c :75°C.

Similar to MP 50 TCM except with PR terminal.

Similar to DC MAXI JOLLY US except for enclosure and t_c :75°C.

Similar to DC MAXI JOLLY US except for different dimmable feature.

Similar to DC MAXI JOLLY US DALI except for enclosure and t_c :75°C.

Similar to DC MAXI JOLLY US except for different dimmable feature.

Similar to DC MAXI JOLLY US MIDNIGHT except for enclosure and t_c :75°C.

Similar to DC MAXI JOLLY US except for different dimmable feature.

Similar to DC MAXI JOLLY US BILEVEL except for enclosure and t_c :75°C.

Similar to DC MAXI JOLLY US except for different dimmable feature.

Similar to DC MAXI JOLLY US BILEVEL N except for enclosure and t_c :75°C.


Similar to DC MAXI JOLLY US except for different dimmable feature.

Similar to DC MAXI JOLLY US PLV except for enclosure and t_c :75°C.

For and on Behalf of
SAA Approvals Pty Ltd

SAA Approvals Pty Ltd Electrical Product Safety Certification Scheme as accredited by JAS-ANZ under ISO/IEC Guide 65 certifies that the electrical product described on this certificate complies with the minimum electrical safety requirements for which the application has been made.

For SAA Contact Details and to verify this Certificate go to:
www.saaapprovals.com.au



www.jas-anz.org/register



141682/2