

Certificate of Suitability

Global-Mark Pty. Ltd., certify the electrical equipment described hereunder complies with standards listed herein and notifies the certificate holder to affix the Regulatory Compliance Mark (RCM) mark on the product of the same type provided that the requirements of all relevant parts of AS/NZS 4417 applicable to the article are fulfilled. In placing the RCM mark on the product, the Responsible Supplier makes a declaration of compliance with the certification standard(s) and confirms that the product is identical to the product certified herein. This Certificate meets the requirements of a Recognised External Certification Scheme (RECS).

CERTIFICATION AND CERTIFICATE HOLDER DETAILS

Company Name	TCI Telecomunicazioni Italia S.R.L.	Other Name	
Address	Via Parma 14 Cap Saronno Varese 21047 Italy		
Client ID	105895	Global-Mark File Number:	105895-105 System 1 Approval
Certification Number	GMA-527336	Revision Number	00
Certificate Standard(s)	AS 61347.2.13:2018 & AS/NZS 61347.1:2016 Amd 1: 2018, Amd 2:2025 Lamp Control Gear - Part 2-13: Particular Requirements For D.C Or A.C Supplied Electronic Control Gear For Led Modules.		
Type of Certification	Electrical Safety Product Scheme	Global-Mark Electrical Product Safety Certification Scheme	

CERTIFICATE DATES

Certificate Issue Date	27/02/2026
Certificate Last Update Date	
Certification Expiry Date	27/02/2031

This certification remains valid until the above-mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jasanz.org/register for verification.



Certification Manager

Henri Hobas



Certificate of Suitability

CERTIFIED ELECTRICAL EQUIPMENT				
Declared Article	Product Description	Trade Name	Model Number	Rating
Non declared	Power Supply for lighting purpose for use with LED lighting	TCI	SVM 110 700-2100 D4i NFC	220-240 V 50-60 Hz 0,55 A Pin=122 W; I _o =0,7-2,1 A Po=110 W U _{out} =60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TCI	SVM 110 700-2100 DALI NFC	220-240 V 50-60 Hz 0,55 A Pin=122 W; I _o =0,7-2,1 A Po=110 W U _{out} =60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TCI	SVM 110 700-2100 1-10V NFC	220-240 V 50-60 Hz 0,55 A Pin=122 W; I _o =0,7-2,1 A Po=110 W U _{out} =60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TCI	SVM 110 700-2100 NFC	220-240 V 50-60 Hz 0,55 A Pin=122 W; I _o =0,7-2,1 A Po=110 W U _{out} =60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TCI	SVM 85 700-2100 110-277V D4i NFC	220-240 V 50-60 Hz 0,43 A Pin=94 W; I _o =0,7-2,1 A Po=85 W U _{out} =60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TCI	SVM 85 700-2100 110-277V DALI NFC	220-240 V 50-60 Hz 0,43 A Pin=94 W; I _o =0,7-2,1 A Po=85 W U _{out} =60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TCI	SVM 85 700-2100 110-277V 1-10V NFC	220-240 V 50-60 Hz 0,43 A Pin=94 W; I _o =0,7-2,1 A Po=85 W U _{out} =60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TCI	SVM 85 700-2100 110-277V NFC	220-240 V 50-60 Hz 0,43 A Pin=94 W; I _o =0,7-2,1 A Po=85 W U _{out} =60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TCI	DC MAXI JOLLY SVM 80 DALI SLIM	220-240 V 50/60 Hz 0,42 A Pin=85 W; I _o =0,35-1,4 A Po=7-78 W U _{out} =60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TCI	DC MAXI JOLLY SVM 80 SLIM	220-240 V 50/60 Hz 0,42 A Pin=85 W; I _o =0,35-1,4 A Po=7-78 W U _{out} =60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TCI	MP 80/1400 SVM SLIM	220-240 V 50/60 Hz 0,42 A Pin=85 W; I _o =0,35-1,4 A Po=7-78 W U _{out} =60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TCI	MP 70/1400 SVM SLIM	220-240 V 50/60 Hz 0,42 A Pin=78 W; I _o =0,35-1,4 A Po=7-70 W U _{out} =59 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TCI	DC MAXI JOLLY SVM 65 DALI SLIM	220-240 V 50/60 Hz 0,33 A Pin=71 W; I _o =0,35-1,4 A Po=7-65 W U _{out} =60 V

This certification remains valid until the above-mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jasanz.org/register for verification.



Certification Manager




Certificate of Suitability

Non declared	Power Supply for lighting purpose for use with LED lighting	TCI	DC MAXI JOLLY SVM 65 SLIM	220-240 V 50/60 Hz 0,33 A Pin=71 W, Io=0,35-1,4 A Po=7-65 W Uout=60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TCI	MP 65/1400 SVM SLIM	220-240 V 50/60 Hz 0,33 A Pin=71 W, Io=0,35-1,4 A Po=7-65 W Uout=60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TCI	MP 65/1150 SVM SLIM	220-240 V 50/60 Hz 0,4 A Pin=71 W, Io=0,35-1,15 A Po=9-65 W Uout=59 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TCI	DC SVM 52/300-1400 DALI NFC	220-240 V 50-60 Hz 0,27 A Pin=58 W, Io=0,3-1,4 A Po=52 W Uout=60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TCI	DC SVM 52/300-1400 NFC	220-240 V 50-60 Hz 0,27 A Pin=58 W, Io=0,3-1,4 A Po=52 W Uout=60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TCI	SVM 52 300-1400 110-277V 1-10V NFC	110-240 V 50-60 Hz 0,27-0,6 A Pin=57 W, Io=0,3-1,4 A Po=52 W Uout=60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TN101	SVM 110 700-2100 D4i NFC	220-240 V 50-60 Hz 0,55 A Pin=122 W; Io=0,7-2,1 A Po=110 W Uout=60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TN101	SVM 110 700-2100 DALI NFC	220-240 V 50-60 Hz 0,55 A Pin=122 W; Io=0,7-2,1 A Po=110 W Uout=60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TN101	SVM 110 700-2100 1-10V NFC	220-240 V 50-60 Hz 0,55 A Pin=122 W; Io=0,7-2,1 A Po=110 W Uout=60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TN101	SVM 110 700-2100 NFC	220-240 V 50-60 Hz 0,55 A Pin=122 W; Io=0,7-2,1 A Po=110 W Uout=60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TN101	SVM 85 700-2100 110-277V D4i NFC	220-240 V 50-60 Hz 0,43 A Pin=94 W, Io=0,7-2,1 A Po=85 W Uout=60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TN101	SVM 85 700-2100 110-277V DALI NFC	220-240 V 50-60 Hz 0,43 A Pin=94 W, Io=0,7-2,1 A Po=85 W Uout=60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TN101	SVM 85 700-2100 110-277V 1-10V NFC	220-240 V 50-60 Hz 0,43 A Pin=94 W, Io=0,7-2,1 A Po=85 W Uout=60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TN101	SVM 85 700-2100 110-277V NFC	220-240 V 50-60 Hz 0,43 A Pin=94 W, Io=0,7-2,1 A Po=85 W Uout=60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TN101	DC MAXI JOLLY SVM 80 DALI SLIM	220-240 V 50/60 Hz 0,42 A Pin=85 W, Io=0,35-1,4 A Po=7-78 W Uout=60 V

This certification remains valid until the above-mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jasanz.org/register for verification.



Certification Manager

Henri Abbas



Certificate of Suitability

Non declared	Power Supply for lighting purpose for use with LED lighting	TN101	DC MAXI JOLLY SVM 80 SLIM	220-240 V 50/60 Hz 0,42 A Pin=85 W, Io=0,35-1,4 A Po=7-78 W Uout=60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TN101	MP 80/1400 SVM SLIM	220-240 V 50/60 Hz 0,42 A Pin=85 W, Io=0,35-1,4 A Po=7-78 W Uout=60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TN101	MP 70/1400 SVM SLIM	220-240 V 50/60 Hz 0,42 A Pin=78 W, Io=0,35-1,4 A Po=7-70 W Uout=59 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TN101	DC MAXI JOLLY SVM 65 DALI SLIM	220-240 V 50/60 Hz 0,33 A Pin=71 W, Io=0,35-1,4 A Po=7-65 W Uout=60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TN101	DC MAXI JOLLY SVM 65 SLIM	220-240 V 50/60 Hz 0,33 A Pin=71 W, Io=0,35-1,4 A Po=7-65 W Uout=60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TN101	MP 65/1400 SVM SLIM	220-240 V 50/60 Hz 0,33 A Pin=71 W, Io=0,35-1,4 A Po=7-65 W Uout=60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TN101	MP 65/1150 SVM SLIM	220-240 V 50/60 Hz 0,4 A Pin=71 W, Io=0,35-1,15 A Po=9-65 W Uout=59 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TN101	DC SVM 52/300-1400 DALI NFC	220-240 V 50-60 Hz 0,27 A Pin=58 W, Io=0,3-1,4 A Po=52 W Uout=60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TN101	DC SVM 52/300-1400 NFC	220-240 V 50-60 Hz 0,27 A Pin=58 W, Io=0,3-1,4 A Po=52 W Uout=60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TN101	SVM 52 300-1400 110-277V 1-10V NFC	110-240 V 50-60 Hz 0,27-0,6 A Pin=57 W, Io=0,3-1,4 A Po=52 W Uout=60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TCI LIGHT Saronno Italy	SVM 110 700-2100 D4i NFC	220-240 V 50-60 Hz 0,55 A Pin=122 W; Io=0,7-2,1 A Po=110 W Uout=60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TCI LIGHT Saronno Italy	SVM 110 700-2100 DALI NFC	220-240 V 50-60 Hz 0,55 A Pin=122 W; Io=0,7-2,1 A Po=110 W Uout=60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TCI LIGHT Saronno Italy	SVM 110 700-2100 1-10V NFC	220-240 V 50-60 Hz 0,55 A Pin=122 W; Io=0,7-2,1 A Po=110 W Uout=60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TCI LIGHT Saronno Italy	SVM 110 700-2100 NFC	220-240 V 50-60 Hz 0,55 A Pin=122 W; Io=0,7-2,1 A Po=110 W Uout=60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TCI LIGHT Saronno Italy	SVM 85 700-2100 110-277V D4i NFC	220-240 V 50-60 Hz 0,43 A Pin=94 W, Io=0,7-2,1 A Po=85 W Uout=60 V

This certification remains valid until the above-mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jasanz.org/register for verification.



Certification Manager




Certificate of Suitability

Non declared	Power Supply for lighting purpose for use with LED lighting	TCI LIGHT Saronno Italy	SVM 85 700-2100 110-277V DALI NFC	220-240 V 50-60 Hz 0,43 A Pin=94 W, Io=0,7-2,1 A Po=85 W Uout=60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TCI LIGHT Saronno Italy	SVM 85 700-2100 110-277V 1-10V NFC	220-240 V 50-60 Hz 0,43 A Pin=94 W, Io=0,7-2,1 A Po=85 W Uout=60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TCI LIGHT Saronno Italy	SVM 85 700-2100 110-277V NFC	220-240 V 50-60 Hz 0,43 A Pin=94 W, Io=0,7-2,1 A Po=85 W Uout=60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TCI LIGHT Saronno Italy	DC MAXI JOLLY SVM 80 DALI SLIM	220-240 V 50/60 Hz 0,42 A Pin=85 W, Io=0,35-1,4 A Po=7-78 W Uout=60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TCI LIGHT Saronno Italy	DC MAXI JOLLY SVM 80 SLIM	220-240 V 50/60 Hz 0,42 A Pin=85 W, Io=0,35-1,4 A Po=7-78 W Uout=60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TCI LIGHT Saronno Italy	MP 80/1400 SVM SLIM	220-240 V 50/60 Hz 0,42 A Pin=85 W, Io=0,35-1,4 A Po=7-78 W Uout=60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TCI LIGHT Saronno Italy	MP 70/1400 SVM SLIM	220-240 V 50/60 Hz 0,42 A Pin=78 W, Io=0,35-1,4 A Po=7-70 W Uout=59 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TCI LIGHT Saronno Italy	DC MAXI JOLLY SVM 65 DALI SLIM	220-240 V 50/60 Hz 0,33 A Pin=71 W, Io=0,35-1,4 A Po=7-65 W Uout=60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TCI LIGHT Saronno Italy	DC MAXI JOLLY SVM 65 SLIM	220-240 V 50/60 Hz 0,33 A Pin=71 W, Io=0,35-1,4 A Po=7-65 W Uout=60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TCI LIGHT Saronno Italy	MP 65/1400 SVM SLIM	220-240 V 50/60 Hz 0,33 A Pin=71 W, Io=0,35-1,4 A Po=7-65 W Uout=60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TCI LIGHT Saronno Italy	MP 65/1150 SVM SLIM	220-240 V 50/60 Hz 0,4 A Pin=71 W, Io=0,35-1,15 A Po=9-65 W Uout=59 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TCI LIGHT Saronno Italy	DC SVM 52/300-1400 DALI NFC	220-240 V 50-60 Hz 0,27 A Pin=58 W, Io=0,3-1,4 A Po=52 W Uout=60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TCI LIGHT Saronno Italy	DC SVM 52/300-1400 NFC	220-240 V 50-60 Hz 0,27 A Pin=58 W, Io=0,3-1,4 A Po=52 W Uout=60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TCI LIGHT Saronno Italy	SVM 52 300-1400 110-277V 1-10V NFC	110-240 V 50-60 Hz 0,27-0,6 A Pin=57 W, Io=0,3-1,4 A Po=52 W Uout=60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TCI LIGHT	SVM 110 700-2100 D4i NFC	220-240 V 50-60 Hz 0,55 A Pin=122 W; Io=0,7-2,1 A Po=110 W Uout=60 V

This certification remains valid until the above-mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jasanz.org/register for verification.



Certification Manager




Certificate of Suitability

Non declared	Power Supply for lighting purpose for use with LED lighting	TCI LIGHT	SVM 110 700-2100 DALI NFC	220-240 V 50-60 Hz 0,55 A Pin=122 W; Io=0,7-2,1 A Po=110 W Uout=60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TCI LIGHT	SVM 110 700-2100 1-10V NFC	220-240 V 50-60 Hz 0,55 A Pin=122 W; Io=0,7-2,1 A Po=110 W Uout=60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TCI LIGHT	SVM 110 700-2100 NFC	220-240 V 50-60 Hz 0,55 A Pin=122 W; Io=0,7-2,1 A Po=110 W Uout=60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TCI LIGHT	SVM 85 700-2100 110-277V D4i NFC	220-240 V 50-60 Hz 0,43 A Pin=94 W, Io=0,7-2,1 A Po=85 W Uout=60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TCI LIGHT	SVM 85 700-2100 110-277V DALI NFC	220-240 V 50-60 Hz 0,43 A Pin=94 W, Io=0,7-2,1 A Po=85 W Uout=60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TCI LIGHT	SVM 85 700-2100 110-277V 1-10V NFC	220-240 V 50-60 Hz 0,43 A Pin=94 W, Io=0,7-2,1 A Po=85 W Uout=60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TCI LIGHT	SVM 85 700-2100 110-277V NFC	220-240 V 50-60 Hz 0,43 A Pin=94 W, Io=0,7-2,1 A Po=85 W Uout=60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TCI LIGHT	DC MAXI JOLLY SVM 80 DALI SLIM	220-240 V 50/60 Hz 0,42 A Pin=85 W, Io=0,35-1,4 A Po=7-78 W Uout=60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TCI LIGHT	DC MAXI JOLLY SVM 80 SLIM	220-240 V 50/60 Hz 0,42 A Pin=85 W, Io=0,35-1,4 A Po=7-78 W Uout=60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TCI LIGHT	MP 80/1400 SVM SLIM	220-240 V 50/60 Hz 0,42 A Pin=85 W, Io=0,35-1,4 A Po=7-78 W Uout=60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TCI LIGHT	MP 70/1400 SVM SLIM	220-240 V 50/60 Hz 0,42 A Pin=78 W, Io=0,35-1,4 A Po=7-70 W Uout=59 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TCI LIGHT	DC MAXI JOLLY SVM 65 DALI SLIM	220-240 V 50/60 Hz 0,33 A Pin=71 W, Io=0,35-1,4 A Po=7-65 W Uout=60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TCI LIGHT	DC MAXI JOLLY SVM 65 SLIM	220-240 V 50/60 Hz 0,33 A Pin=71 W, Io=0,35-1,4 A Po=7-65 W Uout=60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TCI LIGHT	MP 65/1400 SVM SLIM	220-240 V 50/60 Hz 0,33 A Pin=71 W, Io=0,35-1,4 A Po=7-65 W Uout=60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TCI LIGHT	MP 65/1150 SVM SLIM	220-240 V 50/60 Hz 0,4 A Pin=71 W, Io=0,35-1,15 A Po=9-65 W Uout=59 V

This certification remains valid until the above-mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jasanz.org/register for verification.



Certification Manager




Certificate of Suitability

Non declared	Power Supply for lighting purpose for use with LED lighting	TCI LIGHT	DC SVM 52/300-1400 DALI NFC	220-240 V 50-60 Hz 0,27 A Pin=58 W, Io=0,3-1,4 A Po=52 W Uout=60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TCI LIGHT	DC SVM 52/300-1400 NFC	220-240 V 50-60 Hz 0,27 A Pin=58 W, Io=0,3-1,4 A Po=52 W Uout=60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TCI LIGHT	SVM 52 300-1400 110-277V 1-10V NFC	110-240 V 50-60 Hz 0,27-0,6 A Pin=57 W, Io=0,3-1,4 A Po=52 W Uout=60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TCI LED	SVM 110 700-2100 D4i NFC	220-240 V 50-60 Hz 0,55 A Pin=122 W; Io=0,7-2,1 A Po=110 W Uout=60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TCI LED	SVM 110 700-2100 DALI NFC	220-240 V 50-60 Hz 0,55 A Pin=122 W; Io=0,7-2,1 A Po=110 W Uout=60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TCI LED	SVM 110 700-2100 1-10V NFC	220-240 V 50-60 Hz 0,55 A Pin=122 W; Io=0,7-2,1 A Po=110 W Uout=60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TCI LED	SVM 110 700-2100 NFC	220-240 V 50-60 Hz 0,55 A Pin=122 W; Io=0,7-2,1 A Po=110 W Uout=60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TCI LED	SVM 85 700-2100 110-277V D4i NFC	220-240 V 50-60 Hz 0,43 A Pin=94 W, Io=0,7-2,1 A Po=85 W Uout=60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TCI LED	SVM 85 700-2100 110-277V DALI NFC	220-240 V 50-60 Hz 0,43 A Pin=94 W, Io=0,7-2,1 A Po=85 W Uout=60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TCI LED	SVM 85 700-2100 110-277V 1-10V NFC	220-240 V 50-60 Hz 0,43 A Pin=94 W, Io=0,7-2,1 A Po=85 W Uout=60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TCI LED	SVM 85 700-2100 110-277V NFC	220-240 V 50-60 Hz 0,43 A Pin=94 W, Io=0,7-2,1 A Po=85 W Uout=60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TCI LED	DC MAXI JOLLY SVM 80 DALI SLIM	220-240 V 50/60 Hz 0,42 A Pin=85 W, Io=0,35-1,4 A Po=7-78 W Uout=60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TCI LED	DC MAXI JOLLY SVM 80 SLIM	220-240 V 50/60 Hz 0,42 A Pin=85 W, Io=0,35-1,4 A Po=7-78 W Uout=60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TCI LED	MP 80/1400 SVM SLIM	220-240 V 50/60 Hz 0,42 A Pin=85 W, Io=0,35-1,4 A Po=7-78 W Uout=60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TCI LED	MP 70/1400 SVM SLIM	220-240 V 50/60 Hz 0,42 A Pin=78 W, Io=0,35-1,4 A Po=7-70 W Uout=59 V

This certification remains valid until the above-mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jasanz.org/register for verification.



Certification Manager

Henri Hobas



Certificate of Suitability

Non declared	Power Supply for lighting purpose for use with LED lighting	TCI LED	DC MAXI JOLLY SVM 65 DALI SLIM	220-240 V 50/60 Hz 0,33 A Pin=71 W, Io=0,35-1,4 A Po=7-65 W Uout=60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TCI LED	DC MAXI JOLLY SVM 65 SLIM	220-240 V 50/60 Hz 0,33 A Pin=71 W, Io=0,35-1,4 A Po=7-65 W Uout=60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TCI LED	MP 65/1400 SVM SLIM	220-240 V 50/60 Hz 0,33 A Pin=71 W, Io=0,35-1,4 A Po=7-65 W Uout=60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TCI LED	MP 65/1150 SVM SLIM	220-240 V 50/60 Hz 0,4 A Pin=71 W, Io=0,35-1,15 A Po=9-65 W Uout=59 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TCI LED	DC SVM 52/300-1400 DALI NFC	220-240 V 50-60 Hz 0,27 A Pin=58 W, Io=0,3-1,4 A Po=52 W Uout=60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TCI LED	DC SVM 52/300-1400 NFC	220-240 V 50-60 Hz 0,27 A Pin=58 W, Io=0,3-1,4 A Po=52 W Uout=60 V
Non declared	Power Supply for lighting purpose for use with LED lighting	TCI LED	SVM 52 300-1400 110-277V 1-10V NFC	110-240 V 50-60 Hz 0,27-0,6 A Pin=57 W, Io=0,3-1,4 A Po=52 W Uout=60 V

RELEVANT TRADEMARK (S)

COMMENTS OR CONDITIONS ON THE CERTIFICATION

2026/02/27 Initial Certification
- Built-in LED Driver

End of document

This certification remains valid until the above-mentioned expiry date and subject to the organisation's continued compliance with the certification standard, and Global-Mark's Terms and Conditions. This Certificate remains the property of Global-Mark Pty Ltd, Company Number: ACN.108-087-654. The use of the Accreditation Mark indicates accreditation by the Joint Accreditation System of Australia and New Zealand in respect to those activities covered by JAS-ANZ accreditation. Refer to www.jasanz.org/register for verification.



Certification Manager


