

CERTIFICATE ENEC/FI 2018069



Our Ref. 294160-1

Product Electronic control gear for LED module

Rating and principal characteristics See page 2

Trade mark (if any) TCI

Type DC MAXI JOLLY DALI TW 35

Name and address of the licensee and the manufacturer
Helvar Oy Ab
Keilaranta 5
FI-02150 ESPOO
FINLAND

Is in conformity with
EN 61347-2-13:2014 + A1:2017
EN 61347-1:2015
EN 62384:2006 + A1:2009

As shown in the Test Report(s) No(s)
288267-1_A, 288267-1_A Amendment-1, 288267-1_A Amendment-2
288267-1_B, 288267-1_B Amendment-1

It is authorized to use of the marks ENEC 16 and FI

Validity
This certificate is valid until 13 November 2023 provided that the Conditions for ENEC and FI certification are met. This certificate includes the right to use the ENEC 16 and FI mark under the condition that product changes (if any) will be approved at SGS Fimko before the product is brought onto market.

Directive information
The certified product(s) fulfils requirements of above mentioned standard(s) which are harmonised under the Low Voltage Directive (2014/35/EU) at the date of issue of the certificate.

With the following limitations -

Date of issue 13 November 2018

SGS Fimko Ltd

Signature

Joonas Leinonen
Specialist



This certificate has 3 pages



This certificate is issued by the company under its General Conditions for Certification Services accessible at <http://www.sgs.fi/en/Terms-and-Conditions.aspx>. Attention is drawn to the limitations of liability defined therein and in the Test Report here above mentioned which findings are reflected in this certificate. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Fimko Ltd.

Särkiniementie 3 P.O.Box 30 FI-00211 Helsinki, Finland
t. +358 9 696 361 f. +358 9 692 5474 www.sgs.fi

Business ID 0978538-5

Member of the SGS Group (SGS SA)

Page No.: 2 of Certificate No.: ENEC/FI 2018069

**Rating and principal characteristics**

220-240V; 0/50-60Hz; I-LED / U-LED / Prated / λ : 350mA / 12...50V / 17,5W / 0,92 or 700mA / 12...50V / 35W / 0,96; U-OUT: 60V; ta: -20...+50 °C; tc: 75 °C; SELV

Additional information

Model	Trade mark	Classification	Description
DC MAXI JOLLY DALI TW 35	TCI	Built-in	Controlgear with double insulation
DC MAXI JOLLY DALI TW 35 + LC1x70-SR	TCI	Independent	Independent class II controlgear when fitted with an additional associated enclosure part, type LC1x70-SR

LE