









	Article Articolo		Code Codice
	<p><b>CASAMBI CBU-ASD-LR</b></p> <ul style="list-style-type: none"> <li>Bluetooth 4.0 control unit</li> <li>Rated Voltage: 220-240 Vac</li> <li>Vout: 0-10 Vdc (0-10 V) 9-12 Vdc (DALI)</li> <li>Digital output: Standalone DALI</li> <li>Analog output: 0-10 V</li> </ul>	<p><b>CASAMBI CBU-ASD-LR</b></p> <ul style="list-style-type: none"> <li>Unità di controllo Bluetooth 4.0</li> <li>Tensione nominale: 220-240 Vac</li> <li>Vout: 0-10 Vdc (0-10 V) 9-12 Vdc (DALI)</li> <li>Uscita digitale: Standalone DALI</li> <li>Uscita analogica: 0-10 V</li> </ul>	181220
	<p><b>CASAMBI CBU-ASR-C-4423</b></p> <ul style="list-style-type: none"> <li>Bluetooth 4.0 2 Channels Control Unit</li> <li>Rated Voltage: 12-24 Vdc, 30 mA</li> <li>Two 0-10V Output Channels: max. 5 mA each</li> <li>Ideal for Tunable White</li> <li>Sensor input: max. 24 Vdc</li> </ul>	<p><b>CASAMBI CBU-ASR-C-4423</b></p> <ul style="list-style-type: none"> <li>Unità di controllo Bluetooth 4.0 a 2 canali</li> <li>Tensione nominale: 12-24 Vdc, 30 mA</li> <li>Due canali di uscita 0-10 V: max. 5 mA ciascuno</li> <li>Ideali per Tunable White</li> <li>Ingresso sensore: max. 24 Vdc</li> </ul>	181223
	<p><b>CASAMBI CBU-PWM4-LR</b></p> <ul style="list-style-type: none"> <li>Bluetooth 4.0 4 Channels PWM Dimmer for constant voltage loads</li> <li>Rated Voltage: 12-24 Vdc, max. 6 A</li> <li>Output power: max. 144 W @ 24 Vdc; max. 72 W @ 12 Vdc</li> <li>Four PWM Output Channels: max. 6 A</li> <li>Ideal for RGBW and Tunable White</li> </ul>	<p><b>CASAMBI CBU-PWM4-LR</b></p> <ul style="list-style-type: none"> <li>Dimmer PWM 4 canali Bluetooth 4.0 per carichi in tensione costante</li> <li>Tensione nominale: 12-24Vdc, max. 6 A</li> <li>Potenza in uscita: max. 144 W @ 24 Vdc; max. 72 W @ 12 Vdc</li> <li>4 canali di uscita PWM: max. 6 A</li> <li>Ideale per RGBW e Tunable White</li> </ul>	181221
	<p><b>CASAMBI CBU-PWM4-4-C-4027 (UL)</b></p> <ul style="list-style-type: none"> <li>Bluetooth 4.0 4 Channels PWM Dimmer for constant voltage loads</li> <li>Rated Voltage: 12-24 Vdc, max. 4 A</li> <li>Output power: max. 96 W @ 24 Vdc; max. 48 W @ 12 Vdc</li> <li>Four PWM Output Channels: max. 4 A</li> <li>Ideal for RGBW and Tunable White</li> </ul>	<p><b>CASAMBI CBU-PWM4-4-C-4027 (UL)</b></p> <ul style="list-style-type: none"> <li>Dimmer PWM 4 canali Bluetooth 4.0 per carichi in tensione costante</li> <li>Tensione nominale: 12-24Vdc, max. 4 A</li> <li>Potenza in uscita: max. 96 W @ 24 Vdc; max. 48 W @ 12 Vdc</li> <li>4 canali di uscita PWM: max. 4 A</li> <li>Ideale per RGBW e Tunable White</li> </ul>	181222
	<p><b>CASAMBI CBU-TED-LR</b></p> <ul style="list-style-type: none"> <li>Bluetooth Trailing-Edge Dimmer</li> <li>Rated Voltage: 85-240 Vac, max. 0,65 A</li> <li>Output power: max. 150 VA @ 230 Vac; max. 75 VA @ 120 Vac</li> <li>Min. Load: 1 W</li> </ul>	<p><b>CASAMBI CBU-TED-LR</b></p> <ul style="list-style-type: none"> <li>Dimmer Bluetooth a taglio di fase</li> <li>Tensione nominale: 85-240Vac, max. 0,65 A</li> <li>Potenza in uscita: max. 150 VA @ 230 Vac; max. 75 VA @ 120 Vac</li> <li>Carico minimo: 1 W</li> </ul>	181224
	<p><b>CASAMBI CBU-DCS-E-8079</b></p> <ul style="list-style-type: none"> <li>Bluetooth 4.0 control unit</li> <li>Rated voltage: 9,5-22,5 Vdc, 5 mA</li> <li>Powered by a DALI bus</li> <li>Combinable with presence/daylight DALI detectors</li> </ul>	<p><b>CASAMBI CBU-DCS-E-8079</b></p> <ul style="list-style-type: none"> <li>Unità di controllo Bluetooth 4.0</li> <li>Tensione nominale: 9,5-22,5 Vdc, 5 mA</li> <li>Alimentato mediante bus DALI</li> <li>Compatibile con rilevatori DALI di presenza/luminosità</li> </ul>	181225
	<p><b>CASAMBI XPRESS-W-LR-C-239</b> <b>CASAMBI XPRESS-B-LR-C-239</b></p> <ul style="list-style-type: none"> <li>Wireless user interface</li> <li>Rated Voltage: battery (CR2430)</li> <li>Four target buttons</li> <li>Single luminaire &amp; groups control</li> <li>Scenes &amp; animations recall</li> <li>Colour temperature change</li> <li>Direct/Indirect lighting ratio change</li> <li>IP20</li> </ul>	<p><b>CASAMBI XPRESS-W-LR-C-239</b> <b>CASAMBI XPRESS-B-LR-C-239</b></p> <ul style="list-style-type: none"> <li>Interfaccia utente wireless</li> <li>Tensione nominale: batteria (CR2430)</li> <li>4 pulsanti</li> <li>Controllo singola lampada o gruppi</li> <li>Recall di scene e animazioni</li> <li>Variazione temperatura colore</li> <li>Variazione livello di illuminazione diretta/indiretta</li> <li>IP 20</li> </ul>	181230 White 181231 Black
	<p><b>CASAMBI CBU-A2D-E-11503</b></p> <ul style="list-style-type: none"> <li>Bluetooth 4.0 control unit</li> <li>Rated Voltage: 100-277 Vac</li> <li>Vout: 0-10 Vdc (0-10 V) 7 mA 12 Vdc (DALI) 20 mA</li> <li>Digital output: Standalone DALI</li> <li>Analog output 2 CH: 0-10 V</li> <li>Combinable with presence/daylight DALI detectors</li> <li>Ideal for Tunable White</li> <li>IP20</li> </ul>	<p><b>CASAMBI CBU-A2D-E-11503</b></p> <ul style="list-style-type: none"> <li>Unità di controllo Bluetooth 4.0</li> <li>Tensione nominale: 100-277 Vac</li> <li>Vout: 0-10 Vdc (0-10 V) 7 mA 12 Vdc (DALI) 20 mA</li> <li>Uscita digitale: Standalone DALI</li> <li>Uscita analogica 2 CH: 0-10 V</li> <li>Compatibile con rilevatori DALI di presenza/luminosità</li> <li>Ideale per Tunable White</li> <li>IP20</li> </ul>	181228