BLL ACCESSORIES

TCI LED

Made in Italy

BlueLight BLL Link

	Article Articolo	
	**BLL USB DONGLE** • USB-COM adapter • Small size: 43 x 18 mm • BLL range extender (with an external adapter) • Compatible with Windows, Linux and MAC • Compatible with Raspberry PI • Creation of customised gateways or controllers • Beaconing function	**BLL USB DONGLE** • Adattatore USB-COM • Dimensioni ridotte: 43 x 18 mm • Estensore BLL (con adattatore esterno) • Compatibile con Windows, Linux e MAC • Compatibile con Rasberry PI • Creazione di gateway o sistemi di controllo personalizzati • Funzione beaconing
	Code - Codice 135033	
	**MINI BLL GATEWAY** • BLL to Wi-Fi Gateway • Scheduling, Circadian Cycle, Heat Maps, Alexa, Google Home • Cloud update • Ethernet connector for multi-network management • Small size: 75 x 75 x 30 mm • (1) Power supplied not included (1 mt lenght)	**MINI BLL GATEWAY** • Gateway BLL Wi-Fi • Pianificazione, ciclo circadiano, Heat Maps, Alexa, Google Home • Aggiornamento via Cloud • Connettore Ethernet per gestione multi-rete • Dimensioni ridotte: 75 x 75 x 30 mm • (1) Alimentatore non incluso (lunghezza 1 mt)
	Code - Codice 135086 white - 135086B Black (1) **Code - Codice** 162131 white - 162132 black	
	**BLL 2CH ACTUATOR** • Independent use • Normally open, potential free relay • Maximum AC load: 200W • Maximum DC load (resistive): 1A @48 Vdc / 5A @12-24 Vdc • Input voltage: 110 ÷ 127 V; 220 ÷ 240 V	**BLL 2CH ACTUATOR** • Uso indipendente • Relé normalmente aperto a potenziale zero • Massimo carico AC: 200W • Massimo carico DC (resistivo): 1A @48 Vdc / 5A @12-24 Vdc • Tensione di rete: 110 ÷ 127 V; 220 ÷ 240 V
	Code - Codice BLL 2CH ACTUATOR - 135045 BLL 2CH ACTUATOR EX - 135047	
	**SWITCH 3P BLL** (INDEPENDENT MODEL) • Up to 3 normally open programmable push buttons • Maximum cable lenght: 30m • Input voltage: 110 ÷ 127 V; 220 ÷ 240 V • SELV 60 V	**SWITCH 3P BLL** (MODELLO INDIPENDENTE) • Fino a 3 pulsanti normalmente aperti, programmabili singolarmente • Lunghezza cavo: max. 30m • Tensione di rete: 110 ÷ 127 V; 220 ÷ 240 V • SELV 60 V
	Code - Codice SWITCH 3P BLL/2 - 135081 SWITCH 3P BLL EX/2 - 135082	
	**SWITCH 3P BLL** (BUILT-IN MODEL) • Flush mounting boxes or junction boxes • Up to 3 normally open programmable push buttons • Maximum cable lenght: 1m • Input voltage: 110 ÷ 127 V; 220 ÷ 240 V • Dimensions 43 x 43 x 17,5 mm	**SWITCH 3P BLL** (MODELLO BUILT-IN) • Scatole da incasso o di derivazione • Fino a 3 pulsanti normalment aperti, programmabili singolarmente • Lunghezza massima cavo: 1m • Tensione di rete: 110 ÷ 127 V; 220 ÷ 240 V • Dimensioni 43 x 43 x 17,5 mm
	Code - Codice 135080	
	**GATEWAY IOT BLL** • BLL to Wi-Fi Gateway • Scheduling - Heat Maps - Circadian Cycle - Alexa • Ethernet connector • Optional 4G connection	**GATEWAY IOT BLL** • Gateway BLL Wi-Fi • Scheduling - Heat Maps - Ciclo Circadiano - Alexa • Connettore Ethernet • Connessione 4G opzionale
	Code - Codice GATEWAY IOT 4G BLL - 122547BLL GATEWAY IOT BLL - 122556BLL	