









	Article Articolo	
	<b>BLL USB DONGLE</b> <ul style="list-style-type: none"> <li>• USB-COM adapter</li> <li>• Small size: 43 x 18 mm</li> <li>• BLL range extender (with an external adapter)</li> <li>• Compatible with Windows, Linux and MAC</li> <li>• Compatible with Raspberry PI</li> <li>• Creation of customised gateways or controllers</li> <li>• Beaconing function</li> </ul>	<b>BLL USB DONGLE</b> <ul style="list-style-type: none"> <li>• Adattatore USB-COM</li> <li>• Dimensioni ridotte: 43 x 18 mm</li> <li>• Estensore BLL (con adattatore esterno)</li> <li>• Compatibile con Windows, Linux e MAC</li> <li>• Compatibile con Raspberry PI</li> <li>• Creazione di gateway o sistemi di controllo personalizzati</li> <li>• Funzione beaconing</li> </ul>
<b>Code - Codice</b> 135033		
	<b>MINI BLL GATEWAY</b> <ul style="list-style-type: none"> <li>• BLL to Wi-Fi Gateway</li> <li>• Scheduling, Circadian Cycle, Heat Maps, Alexa, Google Home</li> <li>• Cloud update</li> <li>• Ethernet connector for multi-network management</li> <li>• Small size: 75 x 75 x 30 mm</li> <li>• <sup>(1)</sup> Power supplied not included (1 mt lenght)</li> </ul>	<b>MINI BLL GATEWAY</b> <ul style="list-style-type: none"> <li>• Gateway BLL Wi-Fi</li> <li>• Pianificazione, ciclo circadiano, Heat Maps, Alexa, Google Home</li> <li>• Aggiornamento via Cloud</li> <li>• Connettore Ethernet per gestione multi-rette</li> <li>• Dimensioni ridotte: 75 x 75 x 30 mm</li> <li>• <sup>(1)</sup> Alimentatore non incluso (lunghezza 1 mt)</li> </ul>
<b>Code - Codice</b> 135086 white - 135086B Black <sup>(1)</sup> <b>Code - Codice</b> 162131 white - 162132 black		
	<b>BLL 2CH ACTUATOR</b> <ul style="list-style-type: none"> <li>• Independent use</li> <li>• Normally open, potential free relay</li> <li>• Maximum AC load: 200W</li> <li>• Maximum DC load (resistive): 1A @48 Vdc / 5A @12-24 Vdc</li> <li>• Input voltage: 110 ÷ 127 V; 220 ÷ 240 V</li> </ul>	<b>BLL 2CH ACTUATOR</b> <ul style="list-style-type: none"> <li>• Uso indipendente</li> <li>• Relé normalmente aperto a potenziale zero</li> <li>• Massimo carico AC: 200W</li> <li>• Massimo carico DC (resistivo): 1A @48 Vdc / 5A @12-24 Vdc</li> <li>• Tensione di rete: 110 ÷ 127 V; 220 ÷ 240 V</li> </ul>
<b>Code - Codice</b> BLL 2CH ACTUATOR - 135045 BLL 2CH ACTUATOR EX - 135047		
	<b>SWITCH 3P BLL (INDEPENDENT MODEL)</b> <ul style="list-style-type: none"> <li>• Up to 3 normally open programmable push buttons</li> <li>• Maximum cable length: 30m</li> <li>• Input voltage: 110 ÷ 127 V; 220 ÷ 240 V</li> <li>• SELV 60 V</li> </ul>	<b>SWITCH 3P BLL (MODELLO INDIPENDENTE)</b> <ul style="list-style-type: none"> <li>• Fino a 3 pulsanti normalmente aperti, programmabili singolarmente</li> <li>• Lunghezza cavo: max. 30m</li> <li>• Tensione di rete: 110 ÷ 127 V; 220 ÷ 240 V</li> <li>• SELV 60 V</li> </ul>
<b>Code - Codice</b> SWITCH 3P BLL/2 - 135081 SWITCH 3P BLL EX/2 - 135082		
	<b>SWITCH 3P BLL (BUILT-IN MODEL)</b> <ul style="list-style-type: none"> <li>• Flush mounting boxes or junction boxes</li> <li>• Up to 3 normally open programmable push buttons</li> <li>• Maximum cable length: 1m</li> <li>• Input voltage: 110 ÷ 127 V; 220 ÷ 240 V</li> <li>• Dimensions 43 x 43 x 17,5 mm</li> </ul>	<b>SWITCH 3P BLL (MODELLO BUILT-IN)</b> <ul style="list-style-type: none"> <li>• Scatole da incasso o di derivazione</li> <li>• Fino a 3 pulsanti normalment aperti, programmabili singolarmente</li> <li>• Lunghezza massima cavo: 1m</li> <li>• Tensione di rete: 110 ÷ 127 V; 220 ÷ 240 V</li> <li>• Dimensioni 43 x 43 x 17,5 mm</li> </ul>
<b>Code - Codice</b> 135080		
	<b>GATEWAY IOT BLL</b> <ul style="list-style-type: none"> <li>• BLL to Wi-Fi Gateway</li> <li>• Scheduling - Heat Maps - Circadian Cycle - Alexa</li> <li>• Ethernet connector</li> <li>• Optional 4G connection</li> </ul>	<b>GATEWAY IOT BLL</b> <ul style="list-style-type: none"> <li>• Gateway BLL Wi-Fi</li> <li>• Scheduling - Heat Maps - Ciclo Circadiano - Alexa</li> <li>• Connettore Ethernet</li> <li>• Connessione 4G opzionale</li> </ul>
<b>Code - Codice</b> GATEWAY IOT 4G BLL - 122547BLL GATEWAY IOT BLL - 122556BLL		