

# LM280/24E12 - LM560/24E24

Professional series - Linear modules

Made in Italy 

CE US  EN 15

1

UP TO  
**164**  
lm/W

**L80**  
**B20**

> 80.000 h  
@ tc=85 °C / Imax

LINEAR LIGHTING

LM280/24E12



LM560/24E24



**CRI**  
>80  
>90 on request - su richiesta

**Available (CCT) colour temperature**  
3000 K  
4000 K  
5000 K

2700 K on request - su richiesta  
5700 K on request - su richiesta  
6500 K on request - su richiesta

**Beam angle**  
120 °

**Ambient temperature**  
ta: -25...+55 °C  
(Only for tc ≤ 85 °C)

**Module temperature**  
tc max: 85 °C

**Absolute maximum operating current:**  
320 mA

**Standards compliance**  
CSA-C22.2 no.250  
EN 55015  
EN 61547  
EN 62031  
EN 62471  
IEC TR 62778  
UL 8750

Article Articolo	Code Codice	CCT K	Current mA	Flux tc 25°C lm	Flux tc 65°C lm	Power tc 65°C W	Efficacy tc 25°C lm/W	Efficacy tc 65°C lm/W	I <sub>TM21</sub> mA	V <sub>min.</sub> tc 25°C @I <sub>min</sub>	V <sub>max.</sub> tc 25°C @I <sub>max</sub>
LM280/24E12	128165/830H	3000	200	540	510	3,5	153	144	320	17	18,18
			250	660	620	4,5	146	137			
			300	760	710	5,5	137	128			
	128165/840H	4000	200	570	540	3,5	161	153			
			250	690	650	4,5	153	144			
			300	800	750	5,5	145	136			
	128165/850H	5000	200	580	540	3,5	164	153			
			250	700	660	4,5	155	146			
			300	820	770	5,5	148	139			
LM560/24E24	128167/830H	3000	200	1080	1010	7,1	153	143	320	34,1	36,36
			250	1310	1220	9,0	145	135			
			300	1520	1420	11,1	137	128			
	128167/840H	4000	200	1140	1070	7,1	161	151			
			250	1380	1290	9,0	153	143			
			300	1600	1490	11,1	145	135			
	128167/850H	5000	200	1150	1070	7,1	162	151			
			250	1400	1310	9,0	155	145			
			300	1630	1520	11,1	147	137			

The mentioned data can have a 10% tolerance - Il dato indicato può avere una tolleranza del 10%.

## Main features

- Combinable modules for an optimal, extensive design. Perfect light uniformity.
- Ideal for [residential](#), [office](#), [retail and industrial lighting](#).
- SELV modules (Vout < 60 V). Suitable for NON-SELV applications: distance between the voltage area and the board edge ≥ 2,7 mm.
- Extended lifetime > 80.000 h.
- High efficiency: up to 164 lm/W.
- Minimum colour tolerance: 3MacAdam (3SDCM).
- Push-in terminal blocks. Easy module fixing with screws.
- Suitable for emergency applications with TCI inverters.

## Caratteristiche principali

- Moduli combinabili per un design lineare ottimale, anche estensivo. Luce perfettamente uniforme.
- Moduli ideali per [illuminazione residenziale](#), [uffici](#), [spazi commerciali e industriali](#).
- Moduli SELV (Vout < 60 V). Idonei per applicazioni NON SELV: distanza tra parte in tensione e bordo scheda ≥ 2,7 mm.
- Lifetime esteso > 80.000 h.
- Elevata efficienza: fino a 164 lm/W.
- Minima tolleranza di colore: 3MacAdam (3SDCM).
- Morsetti a innesto rapido. Fissaggio del modulo semplice mediante viti.
- Moduli alimentabili in emergenza con inverter TCI.

**7 YEARS WARRANTY**  
3% FAILURE RATE


**10 YEARS WARRANTY**  
5% FAILURE RATE

PRODUCER'S LIABILITY  
TCI


WARRANTY WITH ELECTRONIC  
10 YEARS ACCORDING TO THE EUROPEAN CONDITIONS  
2014

## Technical features - Caratteristiche tecniche

**LM280/24E12** (Weight/Peso 0,74 oz. / gr. 21 - Pcs/Pezzi 48)




**LM560/24E24** (Weight/Peso 1,66 oz. / gr. 47 - Pcs/Pezzi 48)



### Wiring - Cablaggio




0,34 - 0,75 mm<sup>2</sup>



Insert/remove wires by slightly pressing on push-button.  
Inserire/rimuovere i cavi premendo leggermente sul pulsante.

### Accessories - Accessori

**PMMA BOXED LENSES**  
280 mm / 1 ft



Beam Angle Angolo di orientamento	30°	60°	90°	Double asymmetric
Code Codice	468780147	468780148	468780149	468780151

<b>CAPS FOR PMMA BOXED LENSES</b>	<b>Code 488787434</b>
-----------------------------------	-----------------------

To optimise the performance of our LED modules we suggest their use in combination with the lenses of our range. **See section 5.**  
Per una performance ottimale consigliamo l'impiego in abbinamento alle lenti della nostra gamma. **Vedi sezione 5.**

TCI LED modules are not equipped against mains spikes, overloads and short circuits. The use is guaranteed in combination with TCI drivers.  
I moduli LED TCI non sono protetti contro extra tensioni, sovraccarichi e cortocircuiti. L'utilizzo è garantito in combinazione con driver TCI.

#### Dissipation, assembly

A dissipation of the LED module might be required to guarantee the stated datas of brightness and lifetime. Please verify that the modules Tc does not exceed the maximum values as indicated in the table. It is recommended the use of all the holes for the fixing of the LED module or the use of thermoconductive pastes or adhesives. To avoid any damages to the LED module please use only rounded head screws and an additional plastic flat washer. If the LED modules are wired in parallel and a module fails, all the current flowing through the other LED module increases. This may reduce the lifetime of the LED module.

#### Handling and Cleaning

Don't give any shock to the LED modules nor store them in a dusty place. Avoid any contacts with any kind of fluid such as oil or organic solvents. It is recommended the use of IPA (isopropyl alcohol) as solvent to clean the LED modules. Before cleaning, a pre-test should be done to verify any possible damages to the LED module.

#### Static Electricity

Static electricity or surge voltage can damage the LED modules. Always wear anti ESD wrist band or anti ESD gloves when handling the LED modules.

#### Lifetime

The brightness value of a LED module according to 60.000/80.000 working hours is indicated by letter L. Letter B indicates the number of LEDs that keep the L value also after 60.000/80.000 working hours. TCI LED modules are guaranteed L80B20. In other words the 80% of the LEDs will have 80% or higher rendering after 60.000/80.000 working hours.

#### Dissipazione e assemblaggio

Per garantire i dati di luminosità e durata indicati può essere necessaria una dissipazione del modulo LED. Verificare che la Tc del modulo non superi i valori massimi indicati nella tabella. Si consiglia l'utilizzo di tutti i fori previsti per il fissaggio del modulo LED o l'utilizzo di pasta o adesivi termoisolanti. Per non danneggiare i moduli LED utilizzare soltanto viti a testa arrotondata e rondelle plastiche piatte. Se i moduli LED sono collegati in parallelo e un modulo si danneggia, tutta la corrente che passa nell'altro modulo LED aumenta. Questo potrebbe ridurre il lifetime del modulo LED.

#### Uso e pulizia

Non procurare shock ai moduli LED e conservarli in luogo non polveroso. Evitare il contatto con qualsiasi tipo di fluido, come olio o solventi organici. Si raccomanda l'uso di IPA (alcol isopropilico) quale solvente per la pulizia dei moduli LED. Prima di procedere con la pulizia, dovrebbe essere effettuato un pre-test per accertare eventuali danni al modulo LED.

#### Elettricità statica

L'elettricità statica o le tensioni di rete possono danneggiare i moduli LED. Indossare un braccialetto ESD o guanti ESD durante l'uso dei moduli LED.

#### Lifetime

Il valore di luminosità di un modulo LED in base a 60.000/80.000 ore di funzionamento è indicato dalla lettera L. La lettera B indica invece il numero dei LED che rispetteranno il valore L dopo 60.000/80.000 ore di funzionamento. I moduli LED TCI sono garantiti L80B20, che significa che l'80% dei LED avrà una resa pari o superiore all'80% dopo 60.000/80.000 ore di utilizzo.

**For additional technical informations please visit our website: [www.tci.it](http://www.tci.it)**